ACIMENTEIRADOLOURO

PRODUCT TECHNICAL DATA SHEET

SKIRTING 100x495x15 (MOD. 579)

units: mm



Piece Dimensions





Piece Photo

Product characteristics and package	
Colors Available 579/2 579/4 579/6 579/7 579/8	
Dimensions	100x495x15
Items/lm	2 units
Items/Box	24 units
Average weight/Item	1,6 kg
Average weight/lm	3,2 kg
Average weight/Box	38,5 kg

Technical Specifications		
EN 1339 – "Concrete paving flags – Requirements and test methods"		
Intended use	**Internal Flooring**	**External Flooring**
Emission of asbestos	Pass	Not Relevant
Breaking Strength (MPa)	≥ 3,5	≥ 3,5
Slip/ Skid Resistance	Satisfactory	Satisfactory
Thermal Conductivity [W/(mk)]	1,24	Not Relevant
External fire performance	Not Relevant	Not Relevant
Durability	Satisfactory	Satisfactory
Reaction to fire	Classe A1	Not Relevant

Approved	Elaborate	PTDS nº:	Date
Vítor Silva	Bruno Veloso	DECK_003_EN	26/09/2019

A Cimenteira do Louro, S.A. | Ap. 163 E.C. Famalicão
4761-926 V.N. Famalicão, Portugal | Tel. (+351) 252 301 900
www.aclweb.pt
acl@aclweb.pt

Given the characteristics of aggregates and their photographic reproduction, there may be slight variations in particle size and tone.