ACIMENTEIRADOLOURO

PRODUCT TECHNICAL DATA SHEET CE

KIT POOLS - PORTUCALE (MOD. 800 r1500)

Units: mm





Assembly scheme

Product characteristics and package

Colors Available 00 10 20 30 40

Refª.	KIT POOLS	DIMENSIONS Thickness 30/55	AVERAGE WEIGHT
1	BORDER	500 x 330	15,5 kg
2	EXT. CORNER	330 x 330	11 kg
3	R15 INT. CORNER	450 x 330	16,4 kg
4	CURVED CORNER (left)	330 x 330	11,2 kg
5	CURVED CORNER (right)	330 x 330	11,2 kg
6	CURVED BORDER	505/415 x 330	13,8 kg

Technical Specifications

EN 1339 – "Concrete paving flags – Requirements and test methods"

Intended use	Internal Flooring	External Flooring
Emission of asbestos	Pass	Not Relevant
Breaking Strength (MPa)	≥ 3,5	≥ 3,5
Slip/ Skid Resistance	Satisfactory	Satisfactory
Thermal Conductivity [W/(mk)]	1,24	Not Relevant
External fire performance	Not Relevant	Not Relevant
Durability	Satisfactory	Satisfactory
Reaction to fire	Classe A1	Not Relevant

Approved:	Elaborate:	PTDS nº:	Date:
Vítor Silva	Bruno Veloso	KITP_800R1.5_EN	12-01-2022

A Cimenteira do Louro, S.A. | Ap. 163 E.C. Famalicão
4761-926 V.N. Famalicão, Portugal
www.aclweb.pt
acl@aclweb.pt

Given the characteristics of aggregates and their photographic reproduction, there may be slight variations in particle size and tone.