
ACIMENTEIRADOLOURO

PRODUCT TECHNICAL DATA SHEET CE

SMOOTH BLOCK 500 X 200 X 200


Unit: mm



Concrete block for use in masonry, belonging to Category II, according to the harmonized standard EN 771-3 Specification for masonry units - Part 3: Aggregate concrete masonry units (Dense and lightweight aggregates)

Product characteristics

Weight	***17 kg***
Tolerance Category	***D1***
Reaction to Fire	***Class A1***
Mean Compressive strength (MPa)	***≥ 3 N/mm²***
Water Absorption by Capillarity (g/(m2.s))	***≤ 11 g/m².S***
Water Vapour Permeability	***5/15***
Shear Bond Strength (N/mm2)	***0,15 N/mm²***
Dimensional Stability	***≤1,3 mm/m***
Durability Against Freeze / Thaw	**NPD**
Thermal Properties	**NPD**
Acoustical Properties	**NPD**
Units / Sqm	***10***
Unit I Pallet	***60 units***
NPD – No Performance Determined	**NPD – No Performance Determined**


Perspective

Approved by:	**Elaborated by:**	**PTDS nº:**	***Date:***
Dinis Silva	Bruno Veloso	BLFV_03_EN	20/12/2019

A Cimenteira do Louro, S.A. | Ap. 163 E.C.Famalicão – 4761-926 V.N. Famalicão, Portugal | Tel. (+351) 252 301 900 | www.aclweb.pt
acl@aclweb.pt