



Declaration of Performance Nº 2.17_EN

- CIP: 8185 Light Block. (Unique identification code of the product type)
- Masonry Block (Intended use)
- ACL A Cimenteira do Louro, S.A., Monte do Louro, Louro, Ap.163, 4761-926 V. N. Famalicão. (Manufacturer)
- Not Relevant. (Authorized representative)
- System of assessment and verification of constancy of performance 4. (System of assessment and verification of constancy of performance)
- EN 771-3:2011+A1:2015. (Harmonised standard)
- Declared Performance:

Essential Characteristics	Performance			
Dimensions (mm)	500x100x200	500x150x200	500x200x200	400x280x200
Configuration	See PTDS BLL_01_EN			
Tolerance Category	Category D1			
Mean Compressive Strength (MPa)	≥ 1.0			
Dimensional Stability (mm/m)	0,25	0,10	0,19	0,43
Shear Bond Strength (N/mm2)	0,15			
Reaction to Fire	Class A1			
Water Absorption by Capillarity	NPD			
Water Vapour Permeability	5/15			
Gross Density (Kg/m³)	640	491	753	550
Durability Against Freeze / Thaw	NPD			
Dangerous substances	NPD			

8. The performance of the product identified above is in conformity with the set of declared performance (s). This declaration of performance is issued under the sole responsibility of the manufacturer identified above. Manuel Leitão Oliveira e Silva, as Chairman of the Board, signed for and behalf of the manufacturer.

SEDE // HEADQUARTERS UNIDADE DE PRODUÇÃO DE LOURO

GPS N41 26 33 // W8 32 40

R. PDE. DOMINGOS J. PEREIRA, 1284 - LOURO

T. 00351 252 301 900 F. 00351 252 301 929

UNIDADE DE PRODUÇÃO DE LOUSADO PRODUCTION CENTER LOUSADO

GPS N41 22 18 // W8 32 08

R. DA INDUSTRIA, 41 - LOUSADO

T.00351 252 301 000 F.00351 252 301 009

AP. 163 - E.C. FAMALICÃO acl@aclweb.pt